S.C. Johnson Wax Racine, Wisconsin 53403-5011 Phone: (414) 631-2777 Emergency Phone: (800) 228-5635

4=Very High 3=High 2=Moderate 1=Slight

HAZARD RATING HMIS NFPA 0 Health 0 Flammability 0=Insignificant | 0 Reactivity

MATERIAL SAFETY DATA SHEET

,SI	ECTION I-PRODU	UCT IDENTIF	ICATION #31,00,00
PRODUCT NAME: OVER AND UNDER PLUS			PRODUCT CODE 14150-28-30
CHEMICAL OR COMMON NAME NA .	bate issued: 03/18/92 SECTION II-ING	<u> </u>	PREPARED BY: Terry A. Meyers Chemical Info. Adm.
INGREDIENT	S# N/A)	WEIGH 10-20	
 [SARA] Glycol Ether (CAS# 111-90-0	1) 2-5	NOT ECHAPITCHED

111bdcoxyethyl Phosphate (CAS# /8-51-3)	under 2	NOT ESTABLISHED
[PA,NJ,MA] Ammonium Hydroxide (CAS# 1336-21-6)	1-2	25 ppm ACGIH TLV-TWA; 50 ppm OSHA PEL; As Ammonia
Water (CAS# 7732-18-5)	75-85	AM
[SARA,PA,NJ,MA] Glycol Ether (CAS#34590-94-8)		100 ppm ACGIH, TLV-TWA; 150 ppm ACGIH, STEL; 100 ppm OSHA PEL
See Regulatory Information (Section XII) for explanation of bracketed information.		

SECTION III-PHYSICAL DATA Opaque liquid with mild APPEARANCE/ODOR: SPECIFIC GRAVITY (H20=1): 1.03 ammoniacal odor VAPOR PRESSURE (mm Hg): NA PERCENT VOLATILE BY VOLUME (%): NA SOLUBILITY IN WATER: Complete VAPOR DENSITY (Air=1): NA FREEZING POINT (°F): ND BOILING POINT (°F): above 200 рн: 9.0-9.6 EVAPORATION RATE (Butyl Acetate=1): ND VOC (as packaged, minus H2O): ND THEORETICAL VOC (lb/gal): ND

SEC	CTION IV-FIRE AND EXPLOSION INFORMATION	
FLASH POINT (°F) (Method Used):	NA	
FLAMMABLE LIMITS: NA		
EXTINGUISHING MEDIA: Foam.	. CO2. Dry Chemical. Water Fog.	
SPECIAL FIREFIGHTING PROCEDURES: and use caution wher	Normal fire fighting procedures may be used. Cool approaching or handling fire-exposed containers.	[

SECTION IV-FIRE AND EXPLOSION INFORMATION (cont.)	S.C. Johnson Wax 1525 Hove Street Racine, Wisconsin 53403
D EXPLOSION INFORMATION (cont.)	Product Number: 14150 Serial Number: 28-30

Container may burst in heat of fire.

persists, seek medical aid. If product gets on skin, remove with soap and knick complies greater at the control of the control	SIONS AND SIMPLES. Direct contact of product with eyes may cause minor irritation. Prolonged or repeated contact of undiluted product with skin may cause minor irritation. In the skin may cause minor irritation. INSTALL PROCEDURES: Flush eyes with water for 15 minutes. If irritation	PRIMAT ADJE OF EMERT: SKIN CONTACT.
--	--	-------------------------------------

SECTION VI-REACTIVITY DATA

PINBULITY:

STABILITY-COMMITTIONS TO AVOID: None known
NOMATIBILITY: None Known
MAXIONAL DECOMPOSITION PRODUCTS: When exposed to fire, produces normal products of
MUNICOUS PUTHERIZATION: Will not occur.
NAZARDAS POLIMENZATION-CONSTITIONS TO AVOID: None Known

SECTION VII-SPILL OR LEAK PROCEDURES not let spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. No special method. Observe all applicable frederal/State regulations and Local ordinances regarding disposal of non-hazardous materials. Waste from normal product use may be sewered to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements.

PROTECTIVE GLOVES: ENTITATION: RESPURATORY PROTECTION: General room ventilation adequate. special requirements under normal use conditions. If prolonged or repeated contact is possible: Any impervious SECTION VIII-SPECIAL PROTECTION INFORMATION No special requirements under normal use conditions.

HER PROTECTIVE MEASURES:

personal hygiene practices.

MATERIAL SAFETY DATA SHEET

DESCRIPTIONARY LABSTING.	S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403
SECTION IX-SPECIAL PRECAUTIONS	OVER AND UNDER PLUS Product Number: 14150 Serial Number: 28-30
-	PLUS 14150 28-30

PRES RANGERS AND STORAGE CONDITIONS: SECTION X-ADDITIONAL INFORMATION freezing. Store ב ב cool, dry place with adequate

POSTEDNAL SKEDOWSTOM:

X

PRECAUTIONARY LAMELING:

3

<u>8</u>	لغر	וצ	<u> </u>	Г
-	3	or s: NA	-	- 1
Ö,	-	=		ı
53		7	띩	- 1
	ξ	- >	"	- 1
7	- 22	ı	뉟	ı
잌	Ī	- 1	9	
por wores: None	SHIPPING NAME: Buffing or polishing compounds, NOI.	- 1	por class: Non hazardous	- }
	딝		됬	
- 1	H		N	
ı	- 51	- 1	윒	- [
	ωĮ		헲	-
- 1	0		티뜌	
İ	찍	- {	BECTION XI-TRANSPORTATION INFORMATION IOUS	-
	ď		- 13	1
1	읩		19	
1	ᅜ			1
	- 5			- 1
- 1	듸		ال	
	ıق	- 1	2	1
	ol	ì	15	-
ļ	ĝ		166	
İ	윙	- 1	- 18	1
	위		3	
	힐			
- 1	얾		빌	
- 1	-:]	- 1	6	ł
	2		12	
ı	의		lu lu	
		ı	3	
Į	- 1	ŀ	19	
ì			[8	
	- }	- 1	14	ļ
- 1	i		١Ħ	1
ı		- }	\	
	- (ı	- 1	1
- 1				
	ļ	-	-	1
			- 1	1
- }		ļ	i	
			l l	
			Ī	1
1		-		
ı	- 1		1	
- 1		- 1		1

There are no ingredients subject to the reporting requirements under California's Proposition 65.

HA - These ingredients are subject to the reporting requirements under the Massachusetts Hazardous Substance List.

NJ - These ingredients are subject to the reporting requirements under the New Jersey Right to Know Hazardous Substance List.

pA - These ingredients are subject to the reporting requirements under the Pennsylvania Hazardous Substance List.

SARA - These ingredients are subject to the reporting requirements under the Superfund Amendments and Reauthorization Act of 1986 Pitle III, Section 313 and 40 CFR Part 372.

KA-Not Applicable, KE-Not Established, XSR-No Special Requirement, NO-Not Determined
The information herein is given in good faith. No warranty expressed or implied is mode. Any use of these data and
information must be determined by the user to be in accordance with applicable federal, State, and local laws and repulations.
The information contained in this form is confidential and is submitted solely for your organization's internal use.