## MATERIAL SAFETY DATA SHEET

IMPACT PRODUCTS, INC. 2840 CENTENNIAL RD. TOLEDO, OH 43617

Ph: (419)841-2891 Fax: (419)841-7861



	SECTION I
TRADE MAME AND SYNONYMS	
#355M and #655M Mint Freshner Cartridge	Emergency/Information: 419-841-2891
CHEMICAL NAME AND SYNONYMS	
CHENICAL FAMILY	PORMULA

CAS REGISTRY NO.	APPROX.	OSHA PEL ACGIH TLV-IWA
		121 211
		<u> </u>
	CAS REGISTRY NO.	CAS REGISTRY NO. 4 APPROX.

SECTION III - PI	HYSICAL DATA
BOTLING POINT ('P) Data not available	SPECIFIC GRAVITY (H,0=1) 1.12(±0.05)
VAPOR PRESSURE (mm Hg.) Data not available	PERCENT, VOLATILE BY VOLUME (%)
VAPOR DENSITY (AIR=1) Heavier	EVAPORATION RATE
SOLUBILITY IN WATER Insoluble	
AFFEARANCE AND ODOR  Clear coloriess liquid having an odor of wintergreen.	

SECTION IV - FIRE AND	EXPLOSION HAZARD DATA		
FLASH POINT (Method used)	FLAMMABLE LIMITS	LEL	T CL
(Tag closed cup): 205°F	(%volume in air)	Unknown	_Unknown
EXTINGUISHING MEDIA			
CO2, dry chemical or universal-type foam applied acc	cording to manufacturer's tea	chniques.	
SPECIAL FIRE FIGHTING PROCEDURES	_		· · · · · · · · · · · · · · · · · · ·
Wear self-contained breathing apparatus and comple	te personal protective equip	ment.	
UNUSUAL FIRE AND EXPLOSION HARARDS Closed container			
temperatures. If possible, containers should		spray.	

NFPA Codes - Health: 1

Flammability: 1

Reactivity: 0

Page 1

N.E. = Not Established N.A. = Not Applicable

(Continued on Reverse Side)

## SECTION V - HEALTH HAZARD DATA

## THRESHOLD LIMIT VALUE

EFFECTS OF OVEREXPOSURE Ingestion: Harmful if swallowed. Skin Contact: Prolonged contact may lead to irritation and dermatitis. Eye Contact: May cause eye irritation by direct contact or from fumes. Inhalation: May cause respiratory tract irritation.

CHERGENCY AND FIRST AID PROCEDURES Ingestion: If swallowed, drink milk or water and contact a doctor immediately. Skin Contact: Wash skin with soap and plenty of water. Remove contaminated clothing and wash before wearing again. Eye Contact: Flush eyes with water for a least 15 mins. If irritation persists, contact a doctor. Inhalation: Remove victim to fresh air.

			SECTIO	ON VI - REACTIV	ITY DATA	-, <b>-</b>				
	UNSTABLE .	20 0 0 0 0 0	CONDITIONS TO AVOID			agi, valari	Service	W Juney		
	STABLE	<b>X</b>	Sources of igni	ition and/or	excessiv	re heat.	1.0			 
Strong alk		ox c	midizing agent	e.			-		·	
COZ and CC	COMPOSITION P	oduc oduc	ed during comb							
HAZARDOUS	MAY OCCU		CONDITIONS TO AV							 
POLYMERIZATI							1.71.		· .	 ·.

## SECTION VII - SPILL OR LEAK PROCEDURES

steps to be taxen in cast material is released/spilled Small spill: Cover with a non-combustible material and remove to an approved disposal container. Wash area with soap and water. Large Spill: Avoid sources of ignition. Contain spilled material. Cover with a non-combustible material and remove to an approved disposal container. Avoid inhalation of vapors. If in a confined area, NIOSH approved respiratory protection may be required. Wash area with soap and water. Dry products should be swept up and removed to an approved disposal container. Wash area with soap and water.

WASTE DISPOSAL METHOD Dispose of as specified by local, state, or federal regulations.

SECTION VIII - SPECIAL PRO					
RESPIRATORY PROTECTION (Specify type) Not normally reduce to heat use a NIOSH approved respirator.					
VENTILATION LOCAL EXHAUST Meeting ACGIH criteria as ne	eded. SPECIAL				
MECHANICAL (General) Mechanical exhaust					
PROTECTIVE GLOVES	EYE PROTECTION				
Chemical resistant gloves. Use chemical safety goggles or fa					
The state of the s	when eye contact might occur.				
OTHER PROTECTIVE EQUIPMENT Eye wash station and saf Follow good industrial practice as to housekeeping, person	ety shower should be easily accessible.  nal hygicae and avoidance of porlonged or repeated				
contact with skin or syes.	A Company of the Comp				

		( - SPECIAL PRECAU	TIONS	
PRECAUTIONS TO BE TAKEN IN Store in tightly seale	HANDLING AND STORING do containers in a	cool dry place	that is well-venti	lated,
			Freezes er egger	

This information is given in good faith, but no warranty expressed or implied is made. Impact Products believes that it is accurate to the best of its knowledge and relates only to the specific material designated herein.