# MATERIAL SAFETY DATA SHEET



	1. Product and Company Identification			
Product number	165-002			
Product name	Tropic Breeze Air Freshener & Deodorizer			
Effective date	10-Feb-2013			
Company information	Claire Manufacturing Co. 1005 S. Westgate Drive Addison, IL 60101 United States			
Company phone	General Assistance 1-630-543-7600			
Emergency telephone US	1-866-836-8855			
Emergency telephone outside US	1-952-852-4646			
Version #	04			
Supersedes date	02-Dec-2009			
	2. Hazards Identification			
Emergency overview	FLAMMABLE Aerosol. CONTENTS UNDER PRESSURE. Will be easily ignited by heat, spark or flames. Prolonged exposure may cause chronic effects.			
Potential health effects				
Eyes	Contact with eyes may cause irritation.			
Skin	Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).			
Inhalation	Intentional misuse by concentrating and inhaling the product can be harmful or fatal. Prolonged inhalation may be harmful.			
Ingestion	Exposure by ingestion of an aerosol is unlikely. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause delayed lung damage.			
Target organs	Central nervous system. Respiratory system.			
Chronic effects	May cause delayed lung damage. Prolonged skin contact may defat the skin and produce dermatitis.			
Signs and symptoms	Discomfort in the chest. Defatting of the skin. Irritation.			

# 3. Composition / Information on Ingredients

Components	CAS #	Percent
Acetone	67-64-1	60 - 70
Propane	74-98-6	15 - 20
n-Butane	106-97-8	10 - 15
Non-hazardous and other components below reportable levels		1 - 2.5

### 4. First Aid Measures

First aid procedures	
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Get medical attention if irritation develops or persists.
Skin contact	Immediately take off all contaminated clothing. Wash off with warm water and soap. Get medical attention if irritation develops or persists.
Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Ingestion	Have victim rinse mouth thoroughly with water. Do not induce vomiting without medical advice. If vomiting occurs naturally, have victim lean forward to reduce risk of aspiration. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Notes to physician	Symptoms may be delayed.

5. Fire Fighting Measures			
Vapor or gas may spread to distant ignition sources and flash back.			
Water fog. Foam. Alcohol foam. Dry chemical. Carbon dioxide (CO2).			
In the event of fire and/or explosion do not breathe fumes. Wear full protective clothing, including helmet, self-contained positive pressure or pressure demand breathing apparatus, protective clothing and face mask. Containers should be cooled with water to prevent vapor pressure build up. For massive fire, use unmanned hose holders or monitor nozzles; if this is impossible, withdraw from area and let fire burn.			
6. Accidental Release Measures			
Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.			
Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean contaminated surface thoroughly.			
7. Handling and Storage			
Pressurized container: Do not pierce or burn, even after use. Do not handle or store near an open flame, heat or other sources of ignition. Do not smoke while using or until sprayed surface is thoroughly dry. Do not use if spray button is missing or defective. Use only with adequate ventilation. Do not get this material in contact with eyes. Do not get this material in contact with skin. Avoid prolonged exposure.			
Level 3 Aerosol. Contents under pressure. Do not puncture, incinerate or crush. The pressure in sealed containers can increase under the influence of heat. Avoid exposure to long periods of sunlight. Keep in an area equipped with sprinklers. Keep out of the reach of children.			

osure limits ACGIH				
Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	500 ppm	750 ppm	Not established
Propane	74-98-6	1000 ppm	Not established	Not established
n-Butane	106-97-8	1000 ppm	Not established	Not established
OSHA				
Components	CAS #	TWA	STEL	Ceiling
Acetone	67-64-1	1000 ppm	Not established	Not established
Propane	74-98-6	1000 ppm	Not established	Not established

8. Exposure Controls / Personal Protection

#### Personal protective equipment

• • • •	
Eye / face protection	Not normally needed.
Skin protection	Protective gloves.
Respiratory protection	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.

## 9. Physical & Chemical Properties

Appearance	Compressed liquefied gas.
Boiling point	87.8 °F (31.1 °C) estimated
Color	Pale yellow
Density	0.6948 g/cm3 estimated
Flammability (HOC)	32.5488 kJ/g estimated
Flash back	No
Flash point	-156 °F (-104.4 °C) Propellant

Form				
Freezing point	Liquid. Aerosol. Not available			
Odor	Characteristic.			
pH	Not applicable			
Physical state	Liquid.			
Pressure	60 - 70 psig @70°F			
Solubility	Completely			
•	0.6949 estimated			
Specific gravity	0.0949 Estimated			
10.	Chemical Stability & Reactivity Information			
Chemical stability	Risk of ignition. Stable at normal conditions.			
Conditions to avoid	Heat, flames and sparks.			
Hazardous decomposition products	No hazardous decomposition products are known.			
	11. Toxicological Information			
Acute effects	Acute LD50: 29410 mg/kg estimated, Rat, Dermal Acute LC50: 106 mg/l/4h estimated, Rat, Inhalation			
Component analysis - LD50				
Toxicology Data - Selected LD50s a	nd LC50s			
	-64-1 Oral LD50 Rat 5800 mg/kg			
	6-97-8 Inhalation LC50 Rat 658 mg/L 4 h -98-6 Inhalation LC50 Rat 658 mg/L 4 h			
Sensitization	Not expected to be hazardous by OSHA criteria.			
Teratogenicity	Not expected to be hazardous by OSHA criteria.			
	12. Ecological Information			
	•			
Ecotoxicity	LC50 8146 mg/L, Fish, 96.00 Hours,			
	EC50 20585 mg/L, Daphnia, 48.00 Hours, Components of this product have been identified as having potential environmental			
	concerns.			
	13. Disposal Considerations			
Waste codes	D001: Waste Flammable material with a flash point <140 F			
Disposal instructions	Contents under pressure. Do not allow this material to drain into sewers/water supplies. If			
	discarded, this product is considered a RCRA ignitable waste, D001. Dispose in accordance with all applicable regulations.			
	14. Transport Information			
Department of Transportation (DOT)	Requirements			
Basic shipping requirements:				
Proper shipping name	Consumer commodity			
Hazard class	ORM-D			

liazalu ciass	
Subsidiary hazard class	None
Additional information:	
Packaging exceptions	156, 306
Packaging non bulk	156, 306
Packaging bulk	None

#### IMDG

Basic shipping requirements:	
Proper shipping name	AEROSOLS
Hazard class	2.1
UN number	1920
Additional information:	
Packaging exceptions	LTD QTY
Labels required	None

### ΙΑΤΑ

Basic shipping requirements:	
Proper shipping name	Aerosols, flammable
Hazard class	2.1
UN number	1950
Additional information:	
Packaging exceptions	LTD QTY
Labels required	2.1



		15. Regulatory Information		
US federal regulations		This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.		
<b>Occupational Safety and Health</b>	Administratio	on (OSHA)		
29 CFR 1910.1200 hazardou chemical	ı <b>s</b> Yes			
CERCLA (Superfund) reportable	e quantity			
Acetone: 5000.0000				
Superfund Amendments and Re	authorization	Act of 1986 (SARA)		
Section 302 extremely hazardous substance	No	, , , , , , , , , , , , , , , , , , ,		
Section 311 hazardous che	mical Yes			
Hazard categories (311/312)	Delayeo Fire Ha: Pressur	ate Hazard - Yes I Hazard - No zard - Yes e Hazard - Yes ity Hazard - No		
Inventory status				
Country(s) or region	Inventory n	ame	On inventory (yes/no)	
China	-	Existing Chemical Substances in China (IECSC)	N	
Europe	•	uropean Inventory of New and Existing Chemicals (EINECS)		
Europe		uropean Inventory of New and Existing Chemicals (EINECS) No uropean List of Notified Chemical Substances (ELINCS) No		
Japan		Iventory of Existing and New Chemical Substances (ENCS) No		
Korea		kisting Chemicals List (ECL) No		
United States & Puerto Rico		oxic Substances Control Act (TSCA) Inventory Yes		
A "Yes" indicates that all compor		uct comply with the inventory requirements administered by	the governing country(s)	
State regulations				
U.S Pennsylvania - RTK (Rig	ht to Know) List	t		
Acetone	67-64-1	Environmental hazard		
n-Butane	106-97-8	Present		
Propane	74-98-6	Present		
		16. Other Information		
Further information	HMIS T	rademark Statement		
HMIS® ratings	Health: Flamma Physica			

Disclaimer	The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.
MSDS sections updated	Product and Company Identification: Product Review Chemical Stability & Reactivity Information: Hazardous decomposition products
Prepared by	Regulatory Compliance