S.C. Johnson Wax
Racine, Wisconsin 53403-5011
Phone: (414) 631-2777
Emergency Phone: (800) 228-5635
Extension 092

4=Very High
3=High
HMIS NFPA
2=Moderate
1=Slight
0=Insignificant

HAZARD RATING
HMIS NFPA
3 Health
0 Flammability
0 Reactivity

MATERIAL SAFETY DATA SHEET#76,77, 2564 SECTION 1-PRODUCT IDENTIFICATION

PRODUCT NAME: VIREX 128			PRODUCT CODE 13780-4-5 to		
CHEMICAL OR COMMON NAME:			MSDS SECTIONS WITH CHANGES: No significant changes.	PREPARED BY: Terry A.	Meyers Info. Adm.

SECTION II-INGREDIENT INFORMATION					
INGREDIENTS	WEIGHT %	EXPOSURE LIMIT			
Ethanol (CAS# 64-17-5)	1-3	1000 PPM ACGIH/OSHA TWA			
EDTA (CAS# 60-00-4)	1-3	NOT ESTABLISHED			
Octyl Dimethyl Amine Oxide (CAS# 2605-78-9)	1-3	NOT ESTABLISHED			
N-Alkyl Dimethyl Benzyl Ammonium Chloride	3.07	ND .			
Didecyl Dimethyl Ammonium Chloride	4.60	ND			
Water	81-90	NA			
Sodium Hydroxide (CAS# 1310-73-2)	under 1.0	2mg/m3 ACGIH/OSHA Ceiling			
See Regulatory Information (Section XII) for explanation of bracketed information.					

SECTION III	-PHYSICAL DATA		
APPEARANCE/ODOR: Clear, blue liquid with mild antiseptic odor	SPECIFIC GRAVITY (H20×1): 1.01		
VAPOR PRESSURE (mm Hg): ND	PERCENT VOLATILE BY VOLUME (X): 88-90		
SOLUBILITY IN WATER: Complete	VAPOR DENSITY (Air=1): ND		
FREEZING POINT ("F): ND	BOILING POINT (°F): above 200		
рн: 8.0-9.4	EVAPORATION RATE (Butyl Acetate=1): ND		
VOC (as packaged, minus H2O): ND	THEORETICAL VOC (16/gal): ND		

	SECTI	ON IV-F	IRE AND	EXPLOSION	I INFORMATIO	N	
FLASH POINT ("F) (Heti	nod Used):	None	•				
FLAMMABLE LIMITS:	NA						
EXTINGUISHING MEDIA:	Foam. C	02. Dry	Chemic	al. Water	Fog.		
1							

MATERIAL SAFETY DATA SHEET

S.C. Johnson Wax 1525 Howe Street Nacine, Wisconsin 53403

SPECIAL FIREFIGHTING PROCEDURES:

SECTION

IV-FIRE AND Normal fire

EXPLOSION INFORMATION (cont.)

Product Number: 13780 Serial Number: 4-5

FIRE AND EXPLOSION MAZAROS: Container may melt and leak in heat of fire.

Eye SECTION V-HEALTH HAZARD DATA CONTACT. Skin contact.

PRIMARY ROUTE OF EXTRIS

ins the first. Direct contact of product with eyes can cause severe irritation and damage. Direct contact of product with skin can cause irritation. Product may cause severe distress and serious illness if taken

kella, common exeminationate as sense accounts or exposure. Individuals with chronic respiratory disorders such as astima, chronic bronchitis, emphysema, etc., may be adversely affected by exposure to anyvapor or airborne particulate matter. Persons with pre-existing skin disorders be more susceptable to irritating effects. pass an mostpass: If eye contact occurs, flush eyes with water for 15 minutes, then get prompt medical aid. Wash skin with plenty of water. If irritation persists, seek medical aid. If swallowed, drink promptly a large quantity of milk, egg whites, gelatin solution or if these are not evaluable, drink large quantities of water. Avoid alcohol. Get medical Yem

SECTION VI-REACTIVITY DATA

EIVELLI III Stable

ABILITY-COMMITTONS TO AVOID: None known

*COMPTIBILITY: Strong acids (e.g., muriatio acid).

AZARDOUS DECOMPOSITION PRODUCTS: Will not occur When exposed to fire, produces normal products of

AZARDOUS POLTHERIZATION-CONDITIONS TO AVOID: None KNOWN

BECTION VII-BPILL OR LEAK PROCEDURES

FIRST TO BE TAKEN IN CASE MISSIAL IS RELEASED OR PRILED;

TO NOT let Spilled or leaking material enter watercourse. May be toxic to aquatic life. Absorb with oil-dri or similar inert material. Sweep or scrape up and containerize. Rinse affected area thoroughly with water.

For undiluted product: PESTICIDAL WASTE — Observe all applicable Federal/State regulations and local ordinances regarding to a public-owned treatment works (POTW) in compliance with applicable Federal, State, and local pretreatment requirements. may be sewered applicable Observe all

KSPIRATORY PROTECTION: No special requirements under normal use conditions.

MATERIAL SAFETY DATA SHEET

S.C. Johnson Wax 1525 Howe Street Racine, Wisconsin 53403

Page

Product Number: Serial Number:

adequate. INFORMATION

PROTECTIVE GLOVES: γα impervious material.

FIT MOTETION: Chemical workers splash-proof goggles by protection not required unless contact with undiluted product is possible.

FINAL MOTETINE MANAGER: Use good person in hygiene practices. Where grosseye/skin contact may be a problem, wear/use appropriate protective equipment. In case of spills, see Section VII.

PRECUITOMAY LARLING: HAZARDS TO HUMANS AND DOMESTIC BRICALTIONS

Anye damage and severe skin irritation. Do not get in eyes, on skin, or on clothing. To protect eyes wear goggles or face shield and to protect skin, wear rubber gloves when handling. Wash thoroughly with soap and water after handling. Remove contaminated clothing and wash before reuse. Keep from

freezing. Keep out of THER HAMPLING AND STORAGE CONDITIONS: reach Wash thoroughly after handling. of children.

BECTION X-ADDITIONAL INFORMATION

WHITE STATE AND STATE

CLYRE: SECTION XI-TRANSPORTATION INTORNATION CORROSIVE Material (Liquid).

por #: NA 1760

13MM SHIDDING Disinfectants, HOI, VNX \$2.00 H

pot mores: None

MA-Not Applicable, MC-Not Established, MSR-No Special Requirement, MO-Not Determined
The information herein is given in good faith. No warranty expressed or implied it made, any use of these data and into white The information to determine the second of the conditions of the information determined by the user to be in accordance with applicable Federal, State, and local laws and requisitions. The informational internal use. A 100 (law 5 - 10/90)